

PORTABLE CASTERED SUPPORT

Support Width				Height to Top of Conveyor	Weight (Lbs.)
12"	15"	18"	24"		
PCS-12-28	PCS-15-28	PCS-18-28	PCS-24-28	18"-28"	53
PCS-12-40	PCS-15-40	PCS-18-40	PCS-24-40	24"-40"	55
PCS-12-52	PCS-15-52	PCS-18-52	PCS-24-52	30"-52"	57
PCS-12-72	PCS-15-72	PCS-18-72	PCS-24-72	40"-72"	62

Portable Castered Support allows straight sections of gravity skatewheel or 1 3/8 in. dia. roller conveyor to be easily moved.

NOTE: Supplied with 3 in. dia. Hard Rubber stem type brake caster. All weights in catalog are conveyor weights only. Accessories, crating, etc., are not included.



PORTABLE CASTERED CURVE SUPPORT

Support Width				Height to Top of Conveyor	Weight (Lbs.)
12"	15"	18"	24"		
PCCS-12-28	PCCS-15-28	PCCS-18-28	PCCS-24-28	18"-28"	69
PCCS-12-40	PCCS-15-40	PCCS-18-40	PCCS-24-40	24"-40"	71
PCCS-12-52	PCCS-15-52	PCCS-18-52	PCCS-24-52	30"-52"	73
PCCS-12-72	PCCS-15-72	PCCS-18-72	PCCS-24-72	40"-72"	78

Portable Castered Curve Support allows curved sections of gravity skatewheel or 1 3/8 in. dia. roller curves to be easily moved. Floor locks can be supplied—optional, see Page 167.



NOTE: Supplied with 3 in. dia. Hard Rubber stem type brake caster. All weights in catalog are conveyor weights only. Accessories, crating, etc., are not included.

TRIPOD STAND

Adjustable Tripod Stands are used with straight or curved sections of gravity skatewheel and 1 3/8 in. dia. roller conveyor. Optional leg angles can be supplied to fasten stand to floor.

All weights in catalog are conveyor weights only. Accessories, crating, etc., are not included.

- 4 widths
- Portable applications
- Easily Adjusted

CAPACITY DATA:

350 lbs. with 180 in./lbs. of torque on locking screw. (No Shock Loading).

Model No.	Width	Height (Top of Roller/Wheel)		Weight (Lbs.)
		Min.	Max.	
TS-12-18	12"	12"	18"	5 1/2
TS-12-30		18"	30"	8 1/2
TS-12-40		24"	40"	10 1/2
TS-12-52		30"	52"	13 1/2
TS-12-72		40"	72"	19 1/2
TS-12-110		60"	110"	23 1/2
TS-15-18	15"	12"	18"	6
TS-15-30		18"	30"	9
TS-15-40		24"	40"	11
TS-15-52		30"	52"	14
TS-15-72		40"	72"	20
TS-15-110		60"	110"	24
TS-18-18	18"	12"	18"	6 1/2
TS-18-30		18"	30"	9 1/2
TS-18-40		24"	40"	11 1/2
TS-18-52		30"	52"	14 1/2
TS-18-72		40"	72"	20 1/2
TS-18-110		60"	110"	24 1/2
TS-24-18	24"	12"	18"	7
TS-24-30		18"	30"	10
TS-24-40		24"	40"	12
TS-24-52		30"	52"	15
TS-24-72		40"	72"	21
TS-24-110		60"	110"	25



ROLLER STAND

Adjustable Roller Stands are made of heavy gauge pipe with a 1.9 galvanized, ball bearing roller mounted on top. They are used for feeding work to a punch press, saw, drill press, brake press, or anywhere some extra support is required.

- 3 widths
- Portable applications
- Easily Adjusted

MODEL NO.	WIDTH BR	HEIGHT		Weight (Lbs.)
		MIN.	MAX	
ARS-13-18	13"	12 3/8"	18"	9
ARS-13-30		18 3/8"	30"	12
ARS-13-40		24 3/8"	40"	14
ARS-17-18	17"	12 3/8"	18"	10
ARS-17-30		18 3/8"	30"	13
ARS-17-40		24 3/8"	40"	15
ARS-21-18	21"	12 3/8"	18"	12
ARS-21-30		18 3/8"	30"	15
ARS-21-40		24 3/8"	40"	17

All weights in catalog are conveyor weights only. Accessories, crating, etc., are not included.

